

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**

(18)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets

(11) Publication number:

**0 081 913  
B1**

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification: 26.06.85

(51) Int. Cl.<sup>4</sup>: F 25 C 1/00, A 61 J 3/06

(21) Application number: 82306068.6

(22) Date of filing: 15.11.82

(54) Process and apparatus for freezing a liquid medium:

(30) Priority: 11.12.81 GB 8137526

(43) Date of publication of application:  
22.06.83 Bulletin 83/25

(45) Publication of the grant of the patent:  
26.06.85 Bulletin 85/26

(84) Designated Contracting States:  
AT BE CH DE FR IT LI LU NL SE

(56) References cited:  
CH-A- 178 013  
GB-A- 764 718  
GB-A- 927 218  
GB-A-1 251 526  
GB-A-1 316 522  
GB-A-1 320 467  
GB-A-1 340 015  
GB-A-1 548 022  
GB-A-1 594 471  
US-A-2 751 762

(73) Proprietor: JOHN WYETH & BROTHER LIMITED  
Huntercombe Lane South Taplow  
Maidenhead Berkshire, SL6 0PH (GB)

(72) Inventor: Buxton, Ian Richard  
2 Glenmore House Hammersley Lane  
Brambleside  
High Wycombe Buckinghamshire (GB)  
Inventor: Peach, James Marchant  
12 Hylton Road  
High Wycombe Buckinghamshire (GB)

(74) Representative: Brown, Keith John Symons  
et al  
c/o John Wyeth & Brother Limited Patent and  
Trademark Department Huntercombe Lane  
South  
Taplow Maidenhead Berkshire SL6 0PH. (GB)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

Courier Press, Leamington Spa, England.

**EP 0 081 913 B1**

## Description

This invention relates to a process and apparatus for freezing a liquid medium, in particular to a process and apparatus for freezing a liquid medium to give spherical frozen particles.

Freeze drying of liquid mediums, e.g. liquid solutions or suspensions, normally involves freezing the medium and then subsequently subliming the liquid from the frozen material in, for example, a vacuum chamber (freeze drier), to give the freeze dried product. Many methods of freezing are known. For example the liquid medium can be contained in a mould or other container which is cooled with solid carbon dioxide, liquid nitrogen or the like. In an alternative method the mould or other container containing the liquid medium may be passed through a freezing tunnel into which liquid nitrogen is injected, the nitrogen being vapourised and the resulting cold gaseous nitrogen being passed over the liquid medium. In these prior art methods of freezing the liquid is frozen in a container which is wasteful of space both in the freezing apparatus and also in any subsequent processing apparatus such as the freeze drier. In contrast the present invention relates to a process for freezing a liquid medium to give spherical particles of frozen material. These spherical particles may be handled in bulk making the subsequent processing more economical by, for example, saving space in the freeze drier.

It is known, from US Patent Specification 2,751,762, UK Patent Specification 1,251,526 and Swiss Specification 178013, to freeze liquid material, e.g. solutions or water, in pellet or particulate form by injecting the material to be frozen into a body of refrigerant fluid.

According to the present invention there is provided a process for freezing a liquid medium to produce spherical frozen particles in which the liquid medium is introduced in the form of droplets beneath the surface of a cooling liquid which is maintained at a temperature lower than the freezing point of the liquid medium, the cooling liquid being immiscible with, and inert with respect to, the liquid medium, and having a density greater than that of both the liquid medium and the resulting frozen particles such that as the liquid droplets float upwards in the cooling liquid towards the surface thereof they are frozen to form spherical particles characterised in that the cooling liquid is moved in a direction opposite to that of the ascent of the droplets. The frozen spherical particles produced by the process of the invention are of substantially uniform size and constitution.

In the process of the present invention the cooling liquid is moved in a direction opposite to the direction of the ascent of the droplets, i.e. the cooling liquid is moved in a downwardly direction. This has the advantage over the processes described in the prior art that the rate of the ascent of the droplets can be reduced so

enabling *inter alia* more compact apparatus to be used.

The process of the invention is particularly suitable for freezing aqueous solutions or suspensions, especially such solutions or suspensions which require to be subsequently freeze dried. Our French Patent Specification No. 7729663 (Publication 2366835) and our UK Patent Specification 1,548,022 disclose a method of producing shaped articles which are rapidly disintegratable by water and which carry predetermined unit quantities of chemicals by a process involving sublimation of a solvent from a frozen composition comprising the predetermined amount of chemical and a solution in a solvent (especially an aqueous solvent) of a water soluble or water dispersible carrier material so as to give a network of carrier material carrying the chemical. Our European Application 0084705 discloses the preparation of similar solid shaped articles by a process involving sublimation of a solvent from a frozen composition comprising a solution in a solvent of a carrier material and then subsequently dosing the predetermined amount of chemical on to the freeze dried article. The process of the present invention is particularly useful for freezing compositions comprising a solution in an aqueous solvent of a carrier material which upon subsequent freeze drying forms a network which is rapidly disintegratable in water (for example within 5 seconds at 20°C). The compositions may contain a predetermined amount of a chemical such as a pharmaceutical substance and the resulting frozen spherical particles may be freeze dried. If the composition contains a unit dose of chemical then a single freeze dried sphere may constitute a unit dosage which may be administered, dispensed or otherwise utilised in applications where it is desired to employ chemicals (such as pharmaceuticals) in predetermined unit quantities. Alternatively the composition which is frozen may contain less than the unit dosage of chemical and a number of freeze dried spheres would then constitute a unit dosage of chemical. The requisite number of freeze dried spheres can, if desired, be packeted together (e.g. in a sachet or the like) to provide a unit dosage. In an alternative embodiment the composition containing the carrier material without the chemical may be frozen and the frozen spherical particles freeze dried. The chemical may then be dosed on to the resulting freeze dried spheres. This embodiment is particularly advantageous if the amount of chemical to be carried by each sphere is not especially critical (for example in non-pharmaceutical uses, e.g. confectionery). In such applications the chemical may, for example, be sprayed on to the freeze dried spheres.

Examples of suitable carrier materials, particularly those that are pharmaceutically acceptable for use in preparing pharmaceutical dosage forms are given in the above mentioned specifications. For example, the carrier may be formed from polypeptides such as gelatin, par-

ticularly gelatin which is partially hydrolysed, e.g. by heating in water. For example, the gelatin may be partially hydrolysed by heating a solution of the gelatin in water, e.g. in an autoclave at about 120°C for up to 2 hours, e.g. from about 5 minutes to about 1 hour, preferably from about 30 minutes to about 1 hour. The hydrolysed gelatin is preferably used at concentrations of about 1 to 6% weight/vol., most preferably at 2 to 4% e.g. about 3%. Other carrier materials may be used in place of partially hydrolysed gelatin for example polysaccharides such as dextran (in particular dextran of average molecular weight from 60,000 to 275,000 e.g. 150,000 to 200,000), dextrin and alginates (e.g. sodium alginate) or mixtures of above mentioned carriers with each other or with other carrier materials such as polyvinyl alcohol, polyvinylpyrrolidone or acacia. The dextran is preferably used at a concentration of about 4% to 20% weight/volume, e.g. about 6% to 18% (if the mol. weight is 150,000 to 200,000) or about 6% to 10% (if the mol. weight is 200,000 to 275,000).

Besides the chemical and the carrier material the composition to be frozen may contain other additional ingredients. For example, when preparing pharmaceutical dosage forms the composition may include pharmaceutically acceptable adjuvants such as colouring agents, flavouring agents, preservatives and the like. In addition the composition may contain ingredients which aid in the preparation of the shaped articles. For example, the composition may include a surfactant, e.g. Polysorbate 80 BPC [polyoxyethylene (20) sorbitan mono-oleate], to aid in the dispersion of the chemical. The composition may also include ingredients such as fillers (e.g. mannitol, sorbitol) which improve the physical properties of the freeze dried spherical product.

The solvent for the composition is preferably water but it may contain a co-solvent (such as an alcohol) if it is desired to improve the solubility of the chemical.

According to the process of the invention the composition to be frozen is introduced in the form of droplets beneath the surface of a cooling liquid.

Preferably a column of cooling liquid is employed and the composition is introduced near the base of the column. The composition is introduced into the cooling liquid as a liquid drop which floats upwards within the cooling liquid. As it rises the composition is gradually frozen so that the frozen spherical particles may be collected at or near the top of the column. The rate of ascent of the drop and the rate of freezing may be varied by using a cooling liquid of a suitable density and viscosity, maintaining the cooling liquid at the required temperature and employing a column of cooling liquid of suitable length. The length of the column is reduced by circulating the cooling liquid in a direction opposite to the direction of the ascent of the drop (i.e. moving it in a downward direction) so that the rate of the ascent of the drop is reduced.

The cooling liquid should be immiscible with

the liquid medium. If the liquid medium is an aqueous solution or suspension (such as the compositions mentioned above containing a carrier material) the cooling liquid preferably has a density of about 1.05 to 1.4. Preferably the cooling liquid remains liquid to temperatures of at least -50°C in order to provide for sufficiently rapid freezing of the liquid medium. Suitable cooling liquids include trichloroethane, trichloroethylene, dichloromethane, diethyl ether and fluorotrichloromethane.

The liquid medium is introduced under the surface of the cooling medium in the form of liquid drops. For example the liquid medium may be introduced into the cooling medium through an orifice of a size to provide drops of the required size. The size of the spherical frozen particles is also dependant upon the relative densities of the liquid medium and the cooling liquid. In order to prevent the liquid medium freezing around the orifice, the orifice may be maintained at higher temperature than that of the cooling liquid.

The invention also provides an apparatus for use according to the process of the invention. According to the invention an apparatus for freezing a liquid medium to produce spherical frozen particles comprises a container for a cooling liquid, means for maintaining the temperature of the cooling liquid at a temperature below that of the freezing point of the liquid medium, an inlet in the container for introducing the liquid medium in the form of droplets below the surface of the cooling liquid, means for maintaining the temperature of the inlet above that of the freezing point of the liquid medium, means for moving the cooling liquid in a downwardly direction in the container towards the inlet and means for collecting the frozen spherical particles at a position nearer the surface than the inlet. It should be understood that the means for collecting the frozen particles does not necessarily have to be positioned vertically above the inlet, provided that the means are nearer the surface of the cooling liquid than the inlet. Preferably the means are positioned at or near the surface of the cooling liquid.

The container for the cooling liquid is preferably a column of sufficient length to contain the requisite amount of cooling liquid. The column can be jacketed and a heat transfer medium may be circulated through the jacket to maintain the cooling liquid at the desired temperature. The inlet may be in the form of a tube or the like of internal diameter of, for example, 0.5 to 5 mm, e.g. 2 mm. The inlet may be maintained at a higher temperature than the cooling liquid by, for example, an electrical heater or by a heat exchange liquid (e.g. a water bath).

An apparatus in accordance with the invention will now be described with reference to the accompanying drawings in which the Figure is a diagrammatic side elevation of an embodiment of the invention.

In the embodiment shown in the Figure, a vertical column 11 has an inlet 12 near the top and

an outlet 13 near the base so that the cooling liquid 14 circulates in the direction shown by the arrows. The inlet 12 and outlet 13 are protected by filters 15, 16, which allow circulation of the cooling liquid but prevent passage of the spherical particles. Surrounding the column 11 is a jacket 17 through which the heat transfer medium 18 is circulated through an inlet 19 and out through the outlet 20. The heat transfer medium is maintained at a low temperature by passing it through a refrigeration apparatus (not shown).

An inlet pipe 21 for the liquid medium enters the column 11 near its base. The open end of the pipe 21 is surrounded by an electrically heated collar 22.

In the open top of the column 11 there is situated a worm mechanism 23 designed to be driven at about 10 r.p.m. Droplets of liquid medium entering the cooling liquid 14 through the inlet 21 (by means of, for example, a peristaltic pump—not shown) become frozen as they float upwards in the cooling medium and the resulting spherical frozen particles 24 are removed from the top surface of the cooling liquid by the worm mechanism 23. The spheres are dropped by the worm mechanism into a tray 25 in which they may be transported to a cold store or direct to the freeze drier.

The following Examples are reference Examples which illustrate methods for the preparation of frozen spheres and their subsequent freeze drying.

#### Example 1

A 3% w/v hydrolysed gelatin solution is prepared by dissolving 30 g of gelatin B.P. in water (made up to 1000 ml) with heat and constant stirring and autoclaving at 121°C for 60 minutes. After allowing to cool, 30 g of oxazepam and 30 g mannitol is added to form a suspension which is injected by means of a peristaltic pump at a rate of about 5 ml per minute into a cooling liquid. The cooling liquid is dichloromethane maintained at a temperature of about -30°C using trichloroethylene as the heat transfer medium in the jacket. The trichloroethylene is admitted into the top of the jacket at about -40°C and exhausted from the bottom. The trichloroethylene is then pumped through a heat exchange coil immersed in a mixture of alcohol and solid carbon dioxide at a temperature of -78°C and returned to the top of the jacket.

The oxazepam/mannitol/hydrolysed gelatin suspension is pumped into the cooling liquid through a narrow steel tube of about 2.0 mm internal diameter. The base of the column is immersed in a cold water bath to above the level of the steel tube.

As the pump injects the suspension into the cooling liquid droplets rise through the cooling liquid and freeze to form spherical particles which collect in the flared top of the column.

The frozen spheres are removed from the

column, drained and freeze dried in a freeze drier at a pressure of 0.4 mm Hg and a temperature of 60°C for 2 hours.

The resulting freeze dried spheres constitute a pharmaceutical dosage form which dissolve rapidly in water (within 5 secs. at 20°C) and also in the mouth (within 2 seconds). Sixteen of the spheres, each of diameter about 2 to 3 mm constitute a 15 mg dose of oxazepam.

#### Example 2

The procedure of Example 1 is followed replacing the 3% oxazepam by 3.2% lorazepam, to give freeze dried spheres, each of which constitutes a single dose of 1 mg lorazepam.

#### Example 3

The procedure of Example 1 is followed replacing the 3% oxazepam by 0.7% cyclopenthiiazide to give freeze dried spheres, each of which contains 0.25 mg cyclopenthiiazide.

The oxazepam may be replaced by other pharmaceutical substances in particular those disclosed in the above mentioned specifications.

#### Example 4

	w/w
Aluminium hydroxide high strength gel (13%)	15%
Dextran (mw 200,000—275,000)	10%
Mannitol B.P.	3%
Peppermint flavour	0.3%
Thaumatococcus	0.002%
Sodium saccharin	0.02%
Water	to 100%

The above ingredients are mixed thoroughly and pumped at 5 ml/min through a 2 mm orifice into dichloromethane at -15°C to -20°C following the procedure of Example 1. The frozen spheres are recovered from the surface of the solvent and freeze dried in beds up to 2 cm deep. Each sphere contains 5 mg of dried Aluminium Hydroxide Gel and weighs 9 mg. 100 spheres constitute a single dose containing 500 mg dried Aluminium Hydroxide Gel. The spheres constituting a unit dose are dispersed in water by the patient prior to taking.

#### Example 5

The procedure of Example 1 is followed replacing the 3% oxazepam by 2.8% indole acetic acid to give spheres each of which contains 1 mg indole acetic acid. The user can dissolve a sphere in a litre of water to give a composition which can be used as a plant growth promoter.

## Claims

1. A process for freezing a liquid medium to produce spherical frozen particles in which the liquid medium is introduced in the form of droplets beneath the surface of a cooling liquid which is maintained at a temperature lower than the freezing point of the liquid medium, the cooling liquid being immiscible with, and inert with respect to, the liquid medium, and having a density greater than that of both the liquid medium and the resulting frozen particles such that as the liquid droplets float upwards in the cooling liquid towards the surface thereof they are frozen to form spherical particles, characterised in that the cooling liquid is moved in a direction opposite to that of the ascent of the droplets.

2. A process as claimed in Claim 1, in which the frozen spherical particles are collected at or near the upper surface of the cooling liquid.

3. A process as claimed in Claim 1 or 2 wherein the liquid medium is a composition comprising a solution in an aqueous solvent of a carrier material which upon subsequent freeze drying forms a network which is disintegratable in water.

4. A process as claimed in Claim 3 wherein the composition additionally contains a predetermined amount of chemical.

5. A process as claimed in Claim 4 wherein the chemical is a pharmaceutical.

6. A process as claimed in any one of Claims 3 to 5 wherein the carrier material is partially hydrolysed gelatin or dextran.

7. A process as claimed in any one of Claims 3 to 6 wherein the cooling liquid is trichloroethane, trichloroethylene, dichloromethane, diethyl ether or fluorotrichloromethane.

8. A process as claimed in any one of the preceding claims wherein the resulting spherical particles are freeze dried.

9. An apparatus for freezing a liquid medium to produce spherical frozen particles comprising a container (11) for a cooling liquid, means for maintaining the temperature of the cooling liquid at a temperature below that of the freezing point of the liquid medium, an inlet (21) in the container for introducing the liquid medium in the form of droplets below the surface of the cooling liquid, means (22) for maintaining the temperature of the inlet above that of the freezing point of the liquid medium and means (23) for collecting the frozen spherical particles at a position nearer the surface than the inlet characterised in that means (12, 13) are provided for moving the cooling liquid in a downwardly direction in the container towards the inlet.

10. An apparatus as claimed in Claim 9 wherein the container for cooling liquid is a column of sufficient length to contain the requisite amount of cooling liquid.

11. An apparatus as claimed in Claim 9 or 10 wherein the means for maintaining the inlet at the required temperature comprises an electrical heater (22) or a heat exchange liquid.

## Patentansprüche

1. Verfahren zum Gefrieren eines flüssigen Mediums zum Bilden von kugelförmigen gefrorenen Teilchen, bei dem das flüssige Medium in Form von Tröpfchen unterhalb der Oberfläche einer Kühlflüssigkeit eingebracht wird, welche bei einer Temperatur unterhalb des Gefrierpunktes des flüssigen Mediums gehalten wird, wobei die Kühlflüssigkeit mit dem flüssigen Medium nicht mischbar und mit Bezug auf dieses inert ist und eine Dichte aufweist, die größer ist sowohl als jene des flüssigen Mediums als auch der resultierenden gefrorenen Teilchen derart, daß, wenn die flüssigen Tröpfchen in der Kühlflüssigkeit nach oben zur Oberfläche derselben hin schwimmen, sie unter Bildung von kugelförmigen Teilchen gefroren werden, dadurch gekennzeichnet, daß die Kühlflüssigkeit in eine Richtung entgegengesetzt jener des Aufsteigens der Tröpfchen bewegt wird.

2. Verfahren wie in Anspruch 1 beansprucht, worin die gefrorenen kugelförmigen Teilchen an der oberen Fläche der Kühlflüssigkeit oder nahe derselben gesammelt werden.

3. Verfahren wie in Anspruch 1 oder 2 beansprucht, worin das flüssige Medium eine Zusammensetzung ist, die eine Lösung eines Trägermaterials in einem wässrigen Lösungsmittel umfaßt, welche bei anschließendem Gefriertrocknen ein Netz bildet, das in Wasser nicht zersetzbar ist.

4. Verfahren wie in Anspruch 3 beansprucht, worin die Zusammensetzung zusätzlich einen vorherbestimmten Anteil einer Chemikalie enthält.

5. Verfahren wie in Anspruch 4 beansprucht, worin die Chemikalie ein Pharmazeutikum ist.

6. Verfahren wie in einem der Ansprüche 3 bis 5 beansprucht, worin das Trägermaterial partiell hydrolysierte Gelatine oder Dextran ist.

7. Verfahren wie in einem der Ansprüche 3 bis 6 beansprucht, worin die Kühlflüssigkeit Trichloräthan, Trichloräthylen, Dichlormethan, Diäthyläther oder Fluortrichlormethan ist.

8. Verfahren wie in einem der vorhergehenden Ansprüche beansprucht, worin die resultierenden kugelförmigen Teilchen gefriergetrocknet werden.

9. Vorrichtung zum Gefrieren eines flüssigen Mediums zum Bilden von kugelförmigen gefrorenen Teilchen, welche einen Behälter (11) für eine Kühlflüssigkeit, Mittel zum Halten der Temperatur der Kühlflüssigkeit bei einer Temperatur unterhalb jener des Gefrierpunktes des flüssigen Mediums, einen Einlaß (21) im Behälter zum Einbringen des flüssigen Mediums in Form von Tröpfchen unterhalb der Oberfläche der Kühlflüssigkeit, Mittel (22) zum Halten der Temperatur des Einlasses oberhalb jener des Gefrierpunktes des flüssigen Mediums und Mittel (23) zum Sammeln der gefrorenen kugelförmigen Teilchen an einer Stelle näher der Oberfläche als dem Einlaß, dadurch gekennzeichnet, daß Mittel (12, 13) zum Bewegen der Kühlflüssigkeit in eine

Abwärtsrichtung im Behälter zum Einlaß zu vorgesehen sind.

10. Vorrichtung wie in Anspruch 9 beansprucht, worin der Behälter für Kühlflüssigkeit eine Säule mit ausreichender Länge ist, um den erforderlichen Anteil an Kühlflüssigkeit zu enthalten.

11. Vorrichtung wie in Anspruch 9 oder 10 beansprucht, worin die Mittel zum Halten des Einlasses bei der erforderlichen Temperatur eine elektrische Heizvorrichtung (22) oder eine Wärmeaustauschflüssigkeit umfassen.

## Revendications

1. Procédé pour congeler un milieu liquide afin de produire des particules congelées sphériques, dans lequel le milieu liquide est introduit sous forme de gouttelettes sous la surface d'un liquide réfrigérant qui est maintenu à une température inférieure au point de congélation du milieu liquide, le liquide réfrigérant étant immiscible avec le milieu liquide et inerte à l'égard de celui-ci et ayant une densité supérieure à celle du milieu liquide et à celle des particules congelées résultantes, de façon qu'à mesure que les gouttelettes de liquide s'élèvent en flottant dans le liquide réfrigérant vers la surface de celui-ci, elles soient congelées pour former des particules sphériques, caractérisé en ce que le liquide réfrigérant est déplacé dans une direction opposée à celle de l'ascension des gouttelettes.

2. Procédé suivant la revendication 1, dans lequel les particules sphériques congelées sont collectées à la surface supérieure du liquide réfrigérant ou près de celle-ci.

3. Procédé suivant la revendication 1 ou 2, dans lequel le milieu liquide est une composition comprenant une solution dans un solvant aqueux d'un excipient qui, lors de la lyophilisation ultérieure, forme un réseau qui est désintégré dans l'eau.

4. Procédé suivant la revendication 3, dans lequel la composition contient, en outre, une

quantité déterminée au préalable d'un agent chimique.

5. Procédé suivant la revendication 4, dans lequel l'agent chimique est un agent pharmaceutique.

6. Procédé suivant l'une quelconque des revendications 3 à 5, dans lequel l'excipient est la gélatine partiellement hydrolysée ou le dextrane.

7. Procédé suivant l'une quelconque des revendications 3 à 6, dans lequel le liquide réfrigérant est le trichloroéthane, le trichloroéthylène, le dichlorométhane, l'éther diéthylique ou le fluorotrichlorométhane.


8. Procédé suivant l'une quelconque des revendications précédentes, dans lequel les particules sphériques résultantes sont lyophilisées.

9. Appareil pour congeler un milieu liquide afin de produire des particules congelées sphériques, qui comprend un récipient (11) pour un liquide réfrigérant, un dispositif pour maintenir la température du liquide réfrigérant à une température inférieure au point de congélation du milieu liquide, une admission (21) dans le récipient pour introduire le milieu liquide sous la forme de gouttelettes sous la surface du liquide réfrigérant, un dispositif (22) pour maintenir la température de l'admission au-dessus du point de congélation du milieu liquide et un dispositif (23) pour collecter les particules sphériques congelées en un endroit plus proche de la surface que l'admission, caractérisé en ce que des dispositifs (12, 13) sont prévus pour déplacer le liquide réfrigérant en sens descendant dans le récipient en direction de l'admission.

10. Appareil suivant la revendication 9, dans lequel le récipient pour le liquide réfrigérant est une colonne d'une longueur suffisante pour contenir la quantité requise de liquide réfrigérant.

11. Appareil suivant la revendication 9 ou 10, dans lequel le dispositif pour maintenir l'admission à la température requise comprend un organe de chauffage électrique (22) ou un liquide échangeur de chaleur.





**THIS PAGE BLANK (USPTO)**